



# TouchBump™ Specifications

<b>Construction</b>	durable, premium grade polycarbonate enclosure resistant to extreme temperatures, water, grease	
<b>Input Surface</b>	5x2 key membrane, each key rated for 30 million pushes plus touch glidepad for mouse-type functions and gestures metal reinforced top for extended life	
<b>Mounting Options</b>	cost-effective standard QSR bracketing options	
<b>Overlay Options</b>	customizable, removable keypad overlays installed without tools	
<b>Features</b>	right and left click enabled touchpad software programmable scan code definitions adjustable sound for frequency and volume downloadable firmware for updates ConnectSmart ControlPoint support	
<b>Physical</b>	<b>Dimensions</b>	1.25 x 8.25 x 2.75 (H x W x D inches)
	<b>Weight</b>	9.6 ounces
	<b>Connectors</b>	1 Mini-B USB
	<b>Sound</b>	on-board annunciators
<b>Power</b>	provided by controller USB	
<b>Environmental</b>	<b>Operating Temperature</b>	0 to 60° C
	<b>Storage Temperature</b>	-20 to 95° C
	<b>Humidity</b>	10% to 95%, non-condensing
	<b>Altitude</b>	15,000 feet
<b>Connections</b>	<b>Connection Type</b>	USB
	<b>Cable</b>	Mini-B to USB A
	<b>Distance Span</b>	15 feet (per USB spec)
<b>Safety and Certifications</b>	<b>FCC</b>	Class A, Part 15
	<b>CE</b>	EN55024
		WEEE, EU RoHS, China RoHS, MIC